

P.O. Box 599 - Mars, PA 16046 800-321-3337

## Material Safety Data Sheet

QUICK IDENTIFIER: BUTYL RUBBER TAPE

IN PLANT COMMON NAME: ST-30

MANUFACTURER: EMERGENCY TELEPHONE NO: (800) 321-3337

FBC CHEMICAL CORP.

P.O. BOX 599 MARS, PA 16046

PREPARED BY: Jonathan M. Lawrence DATE PREPARED: JANUARY, 2003

**SECTION I - IDENTITY** 

TRADE NAME: LAURENCO ST-30 (Liquid Applied Membrane) CAS# NONE (MIXTURE)

CHEMICAL NAME: BUTYL RUBBER TAPE.

CHEMICAL FAMILY: BUTYL RUBBER.

FORMULA: EXTRUDED BUTYL RUBBER BLEND.

**SECTION II - HAZARDOUS INGREDIENTS** 

PRINCIPAL HAZARDOUS COMPONENTS AND COMMON NAMES		%	OSHA PEL	THRESHOLD LIMIT VALUE
BUTYL RUBBER	CAS# 9010-85-9	79 - 94	N/A	N/A
QUARTZ (SiO <sub>2</sub> )	CAS# 14808-60-7	<1	AS DUST	0.1 MG/M <sup>8</sup>
CARBON BLACK	CAS# 13333-86-4	5 - 20	AS DUST	3.5MG/M <sup>3</sup>

INFORMATION FOR MIXTURES IS BASED IN CONSTITUENT MSDS WHICH ARE AVAILABLE UPON REQUEST.

## SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS (FIRE EXPLOSION DATA)

BOILING POINT: N.A.

SPECIFIC GRAVITY (H2O=1):

1.30

VAPOR PRESSURE (MM HG): N.A.

PERCENT VOLATILE BU VOLUME (%): N.A.

VAPOR DENSITY (AIR=1): N.A.

EVAPORATION RATE: N.A.

SOLUBILITY IN WATER: NONE

REACTIVITY IN WATER: NONE

APPEARANCE & COLOR: DARK COLOR, SOLID

N.E.P.A.: HEALTH=0, FLAMMABILITY=0, REACTIVITY=0, PERSONAL PROTECTION=A

FLASHPOINT: 325F SETA

FLAMMABLE LIMITS IN AIR % BY VOLUME: LOWER N.A.%, UPPER N.A.%

A75000 BUTYL TAPE PAGE 1 OF 3



EXTINGUISHER MEDIA: DRY CHEMICAL FOAM

AUTO IGNITION TEMPERATURES: >400F

SPECIAL FIRE FIGHTING PROCEDURE: DRY CHEMICAL, FOAM, WATER FOG

UNUSUAL FIRE & EXPLOSION HAZARDS: NONE KNOWN. TREAT AS A CLASS "B" FIRE.

**SECTION IV - PHYSICAL HAZARDS** 

STABILITY: STABLE

CONDITIONS TO AVOID: OPEN FLAME

INCOMPATIBILITY (MATERIALS TO AVOID): ACID, CAUSTICS, OXIDIZERS

HAZARDOUS DECOMPOSITION PRODUCTS: NITROGEN OXIDES, CARBON OXIDES

HAZARDOUS POLYMERIZATION: N/A

**SECTION V - HEALTH HAZARDS** 

THRESHOLD LIMIT VALUE: MIXTURE

PRIMARY ROUTE OF ENTRY TO BODY: SKIN

SIGNS OF SYMPTOMS OF EXPOSURE: IRRITATION OF SKIN.

MEDICAL CONDITIONS: NOT KNOWN.

CHEMICAL LISTED AS CARCINOGEN: N.A., MIXTURE

EXPOSURE LIMIT: NOT KNOWN

ACGIII THRESHOLD LIMIT VALUE: MIXTURE

OTHER EXPOSURE LIMIT USED: SEE LOWEST INGREDIENT LEVEL

EMERGENCY AND FIRST AID PROCEDURES: EXPOSURE TO SKIN IF RASH OCCURS MAY REQUIRE

FLUSHING WITH LARGE AMOUNTS OF WATER IMMEDIATE EMERGENCY TREATMENT. CONTACT WITH EYES TREAT AS

FOREIGN OBJECT.

INHALATION: N.A.

EYES: FLUSH EYES FOR 15 MINUTES WITH CLEAN WATER. GET MEDICAL TREATMENT

SKIN: WASH WITH SOAP AND WATER OR WATER LESS HAND CLEANER. IF IRRITATION PERSISTS, GET

MEDICAL ATTENTION

INGESTION: DO NOT INDUCE VOMITING!!! GET MEDICAL ATTENTION QUICKLY!

SECTION VI - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): N.A.

VENTILATION: OUTSIDE; NOT NEEDED: IF INSIDE: NOT NEEDED

MECHANICAL (GENERAL): IF INSIDE SPECIAL: NOT NEEDED

A75000 BUTYL TAPE PAGE 2 OF 3



PROTECTIVE GLOVES: NOT NEEDED

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS IF NEEDED.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NOT NEEDED

SECTION VII - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: USE IN WELL VENTILATED AREA. STORE IN

DRY, COOL PLACE

OTHER PRECAUTIONS: DO NOT HEAT MATERIAL FOR APPLICATION.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SOLID, WILL NOT SPILL.

WASTE DISPOSAL METHODS: RCA REGULATED MATERIAL. CONSULT LOCAL, STATE AND FEDERAL

REGULATION PERMITTED LANDFILL DISPOSAL OR INCINERATION.

A75000 BUTYL TAPE PAGE 3 OF 3