



Laurenco Waterproofing, A Division of FBC Chemical
P.O. Box 599 Mars, PA 16046
Ph: (800) 321-3337
www.laurencowaterproofing.com

PMMA Consumption Rates

Layer	SF/UNIT	kg/SF	kg/SQ	kg/m ²
Primer R (Asphalt)	270 SF / 10 kg Pail	0.037 kg/SF	3.7 kg/SQ	0.4 kg/m ²
Primer W (Concrete)	270 SF / 10 kg Pail	0.037 kg/SF	3.7 kg/SQ	0.4 kg/m ²
Primer W (DensDeck & DensDeck P)	135 SF / 10 kg Pail	0.074 kg/SF	7.4 kg/SQ	0.8 kg/m ²
Laurenco PMMA Base/Fleece/Top (smooth substrate)	32 SF / 10 kg Pail	0.019 kg/SF	18.6 kg/SQ	2.0 kg/m ²
Laurenco PMMA Base/Fleece/Top (granular surface)	25 SF / 10 kg Pail	0.28 kg/SF	27.9 kg/SQ	3.0 kg/m ²
Laurenco PMMA Flashing Resin Wearing Surface (for embedment of granule surfacing)	110 SF / 10 kg Pail	0.09 kg/SF	9.0 kg/SQ	1.0 kg/m ²

**Rates above are for estimating purposes only & do not include waste, overage due to uneven surfaces, or extra material required to address unforeseen conditions.