

NOTES:
 1. LAURENCO PMMA LIQUID FLASHING MAY BE UTILIZED IN LIEU OF MEMBRANE FLASHING PLIES.
 CONTACT LAURENCO TECHNICAL DEPARTMENT FOR SPECIFIC REQUIREMENTS AND DETAILS.

LAURENCO OR APPROVED DRAINAGE COMPOSITE,
 WRAP FILTER FABRIC UNDERNEATH AT END

ONE OR TWO LAYERS (AS SPECIFIED) LAURENCO
 SPC OR PPC PROTECTION SHEET, FULLY ADHERE

Prefix 0.1957 IN.

(E) PROTECTION LAYER

ALUMINUM THRESHOLD ANCHORED TO CONCRETE
 CURB WITH SEALANT AT FASTENERS (BY OTHERS)
 CONCRETE DOWEL (BY OTHERS)

METAL COPING (BY OTHERS)

TRAFFIC GRADE SEALANT OVER COMPRESSIBLE FOAM STRIP (BY OTHERS)
 SUITABLE SURFACING (BY OTHERS) - PAVERS OVER CONCRETE SAND
 OVER COMPACTED AGGREGATE SHOWN, ADDITIONAL SURFACINGS
 TYP. INCLUDE CONCRETE TOPPING, AGGREGATE, TILE OVER
 MORTAR BED OR TERRAZZO.

(E) TWO PLY FOOTER
 WATERPROOFING

(E) TWO PLY BASE FLASHING
 WATERPROOFING

(E) TWO PLY WATERPROOFING
 (E) SLOPED MODIFIED MORTAR
 LAURENCO TWO PLY WATERPROOFING

LAURENCO TWO PLY
 FOOTER WATERPROOFING

LAURENCO TWO PLY BASE
 FLASHING WATERPROOFING
 CONCRETE (BY OTHERS)
 SLOPED MODIFIED MORTAR

LAURENCO TWO PLY WATERPROOFING

MEMBRANE TIE-IN AT THRESHOLD AT PASSAGE